

# Bomanite®

## Revealed Glass Series Standard Color Chart

COLOR FOR:

EXPOSED AGGREGATE  
SYSTEMS


ENGINEERED  
CONCRETE FOR  
HIGHLY  
DECORATIVE  
AND DURABLE  
FINISHES






# Bomanite Revealed Glass Series Color Chart

## STANDARDS




EX-RV-080211-11




EX-RV-080211-06




EX-RV-080211-19




EX-RV-080211-12




EX-RV-080211-02




EX-RV-080211-09




EX-RV-080211-14



EX-RV-080211-13



EX-RV-082211-01



EX-RV-080211-18



EX-RV-080211-16



EX-RV-080211-20

## IMPORTANT NOTES:

Bomanite Revealed utilizes natural and man-made aggregates, encapsulated in an engineered binder, and applied monolithically to freshly placed concrete. Use the Bomanite Coloration Systems Standard Color Chart for Bomanite Revealed base colors. Aggregates typically used for Bomanite Revealed are 1/8" through 3/4" in size with 1/4" to 3/8" considered optimal. The use of aggregates outside this size range may require the use of a different Bomanite process such as Bomanite Sandscape or a customized Bomanite Revealed product and process. Standard blends incorporating recycled glass aggregates are pictured, however custom blends are commonplace.

Variations of the aggregates in Bomanite Revealed from pour to pour and within pours themselves may include, but are not limited to; size, shape, color, texture, gloss and aggregate exposure. The finished Bomanite Revealed may have areas with more or less aggregate showing through the surface of the concrete. The aggregate concentration may also vary throughout the concrete surface with occasional areas of fine sands only being exhibited. Periodically native sands or aggregates in the concrete mix may be seen on the surface of Bomanite Revealed around the decorative aggregates. The color of Bomanite Revealed can vary from pour to pour slightly due to factors such as, but not limited to; ambient temperature, relative humidity, water content of both the Revealed and the concrete slab it is being incorporated onto, moisture content of the sub-base as well as sub-base type, early exposure to rain or sun, color of decorative aggregates used in the mix.

It is strongly recommended that samples be created, viewed and approved using construction techniques and materials identical to those that will be used in the actual construction of the project. This sampling process must be completed prior to specifying the final color and appearance. Bomanite Revealed is only available through Bomanite Exposed Aggregate Concrete Licensed Contractors.

# Bomanite®

The Bomanite Company  
8789 Auburn Folsom Rd. #108  
Granite Bay, CA 95746  
(303) 369-1115 Fax: (303) 291-0282  
[www.bomanite.com](http://www.bomanite.com)

©2011 The Bomanite Company. Bomanite® is a registered trademark and servicemark with the U.S. Patent Office and other countries. 5C0911

Chart 900.11

Your authorized Bomanite Exposed Aggregate Licensed Contractor is: